

**CARATTERISTICHE MINIME ROUTER COMPATIBILI PER LE TECNOLOGIE FIBRA E WFA (*Wireless Fixed access*)**

<b>WAN</b>	1 x GigE, RJ45
<b>LAN</b>	4 x GigE, RJ45
<b>WiFi</b>	2x2 Dual band 11ac 2.4 (11n) and 5 GHz (11ac)
<b>ATA - for Voice (per servizio Voip)</b>	Almeno una porta FXS
<b>Protocolli</b>	<p><b>Routing</b></p> <ul style="list-style-type: none"> <li>- DHCP/ PPPoE/ Static IP</li> <li>- Dynamic DNS/DNS SRV (RFC 1706 and RFC 2782)</li> <li>- NAT Traversal (Static NAT Route or by STUN)</li> <li>- DHCP Client and DHCP server</li> <li>- Support IEEE 802.1Q VLAN/802.1p</li> </ul> <p><b>Voip QoS</b></p> <ul style="list-style-type: none"> <li>- Layer 3 (DSCP) settings for SIP, RTP and Data</li> </ul> <p><b>Security</b></p> <ul style="list-style-type: none"> <li>- WEP, WPA-PSK (TKIP), WPA-PSK (AES), WPA2-PSK (TKIP), WPA2-PSK (AES), Mixed mode</li> </ul>